

Outputs	
2 ohms Stable	Yes
Output per Channel into 8 ohms at 1 kHz	800 W
Output per Channel into 4 ohms at 1 kHz	1200 W
Output per Channel into 2 ohms at 1 kHz	1800 W
Bridge Output into 8 ohms at 1 kHz	2400 W
Bridge Output into 4 ohms at 1 kHz	3600 W
Output Channels	2
Output Mode	Bridge, Mono, Parallel, Stereo
Output Connector	Speaker Connector 4 pole
Inputs	
Mono Inputs	2
Mono Input Connector	3-pin XLR
Mono Input Impedance	20000 Ω
Balanced Mono Input Sensitivity	32 dBu
Audio Specifications	
THD Level	< 0.05 %
Signal-to-noise Ratio	> 100 dB
Slew Rate	50 V/μs
Amp Technology	Class D
Damping Factor	1000 :1
Crosstalk	75 dBu
Frequency Response Minimum	20 Hz
Frequency Response Maximum	20000 Hz
Electrical Specifications and Connections	
Power Supply	100-240 V AC 50/60 Hz
SMPS	Yes
Power Consumption	720 W

Power Connector In		IEC
Mechanical Specifications		
Height (mm)		45 mm
Width (mm)		483 mm
Length (mm)		296 mm
Installation Depth (Excl. Connector)		296 mm
Flightcase Size		19"
Rack Units		1 U
Housing		Steel
Colour		Black
Finish		Powder Coating
Weight		5.2 kg
IP Rating		IP20 (indoor use only)
Product Properties		
Electronic Protection		Clip limiter, DC voltage, Overheat, Overload, Under voltage
LED Indicators		Clip, Power, Protect, Signal
Thermal Specifications		
Maximum Ambient Temperature		40 °C
Minimum Ambient Temperature		-15 °C
Maximum Surface Temperature		70 °C
Included Items		
Included Cables		IEC cable
Included Accessories		Rubber feet