

## Product Specifications

<b>CCT</b>	2,300K – 10,000K
<b>CRI</b>	≥95
<b>TLCI</b>	≥98
<b>CQS</b>	96
<b>SSI (Tungsten)</b>	85
<b>SSI (D56)</b>	74
<b>TM-30 RF (Average)</b>	93
<b>TM-30 RG (Average)</b>	101
<b>Max Power Consumption</b>	720W
<b>Max Power Output</b>	600W
<b>Weather Resistance Rating</b>	IP54
<b>Reflector Beam Angle</b>	45°
<b>Operating Voltage (Two Batteries)</b>	12-33.6V
<b>Operating Voltage DC</b>	48V / 15A
<b>Operating Voltage PSU</b>	100V~240V/8A/50-60Hz
<b>Operating Temperature</b>	-20°C ~ 45°C / -4°F ~ 113°F
<b>Storage Temperature</b>	-40°C ~ 85°C / -40°F ~ 185°F
<b>Firmware Upgradeable</b>	Sidus Link, USB Drive
<b>Wireless Range (Bluetooth)</b>	≤80m / ≤262.5ft
<b>Screen Type</b>	TFT
<b>Cooling Method</b>	Active Cooling
<b>Control Methods</b>	
<b>Control Methods</b>	On-board, Sidus Link App, DMX/RDM, CRMX, etherCON
<b>Noise Levels</b>	
<b>Lamp Head Fan Noise Levels Smart Mode</b>	32.9dBa
<b>Lamp Head Fan Noise Levels High Mode</b>	32.9dBa
<b>Lamp Head Fan Noise Levels Medium Mode</b>	30.0dBa
<b>Lamp Head Fan Noise Levels Silent Mode</b>	24.0dBa
<b>Control Box Noise Level All Modes</b>	28.0dBa
<b>Weight</b>	
<b>Lamp Head With Yoke</b>	5.9 kg / 13.0lbs
<b>Control Box</b>	5.4 kg / 11.9lbs
<b>Dimensions</b>	
<b>Lamp Head With Yoke</b>	45.2 x 26.7 x 15.0cm 17.8 x 10.5 x 5.9in
<b>Control Box</b>	36.6 x 19.7 x 15.6cm 14.4 x 7.8 x 6.1in