



- Special features**
- Can be dimmed using leading-edge/trailing-edge phase dimmers
 - Ideal for retrofitting existing installations, since it can be dimmed primarily with rotary/push-button dimmers [C-compatible]
 - Cannot be combined with PWM dimmers such as RF, DMX, DALI or KNX
 - Robust housing
 - Flicker-free
 - Secured against short circuits and overloads
 - Overheating protection

Housing Material	Aluminium
Housing Color	Silver
Functions	Short-circuit proof, Lamp control gear 110, Furniture installation, Protective extra-low voltage, Overloading protection, Overtemperature protection
Operating Mode	Constant voltage
Protection Class	Protection class I/protective grounding
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power	66.0-200 W
Output Voltage	48 V/DC
Output Current	1380-4160 mA
Dimmable	Yes
Control	Leading-edge dimmer, Trailing-edge dimmer
Number of Channels	1
Power Factor	0.95
Max. units per MCB B10	2
Max. units per MCB B16	3
Max. units per MCB C10	4
Max. units per MCB C16	7
Inrush Current max.	25 A / 300 µs
Capacitive Load	6.6 µF
Reference Point Tc	80 °C
Working Temperature	-20 to 50 °C
Storage Temperature	-20 to 50 °C
IP Protection Class	IP 67
Length	249 mm
Width	72 mm
Height	40 mm
Product weight	1250 g

