



Compact 230 W cold white follow spot

EAN: 8717748620248



The Showtec ACT Follow Spot 230 CW is a compact and powerful LED follow spot equipped with a 230 W cold-white LED engine (6000 K). It features an internal colour wheel offering a choice of 4200 K, 3200 K, lavender, amber and pink, or open white for maximum output. The fixture includes a motorised iris, as well as dimmer and strobe functions, all controllable via DMX or a dedicated panel. The manual zoom (8°-32°), manual focus, and manual shutters provide full control over beam shape and size, while a gobo slot adds creative flexibility for marking, framing or pattern projection. A clear OLED display on the unit makes setup and configuration straightforward.

The dedicated control panel is included and offers six direct-access colour buttons and three faders for dimmer, iris and strobe. The controller can be mounted on the side or the back of the unit using the supplied metal clamp. The fixture also provides DMX in/out with merge, allowing control from both a lighting desk and the included panel at the same time-ideal for situations where the lighting operator needs both local and desk-based control.

Special features:

- 230 W cold-white LED (6000 K) with CRI 90
- Colour wheel with 6000 K, 4200 K, 3200 K, lavender, amber and pink
- Motorised iris with DMX control
- Manual zoom from 8° to 32°
- DMX512 with merge function + dedicated controller included

Specifications:

Source

Light Source Type	LED
Light Source Quantity	1
Light Source Power	230 W
LED Colour Type	CW
Refresh Rate	1000 Hz
Illuminance @ 2 m	6608 lx
Illuminance @ 3 m	2937 lx
Illuminance @ 5 m	1057 lx
Luminous Flux (Total)	6513 lm
CRI	90
CCT	6000 K

Optical

Beam Angle Minimum (Circular)	8.3°
Beam Angle Maximum (Circular)	32.4°
Zoom Type	Manual
Zoom Minimum	8°
Zoom Maximum	32°
Iris	Motorised

Control and Programming

Control Mode	DMX / Manual
DMX Channels	4 / 5
Protocols	DMX / RDM
Display	OLED
Display Size	1.3"
Dim Curve	Square / I-Square / S-Curve
Dimmer Resolution	16 bit

Dynamic Effects

Dimmer	0-100 %
Strobe	0-15 Hz
Colour System	Colour Wheel

Electrical Specifications and Connections

Power Supply	100-240 V AC 50/60 Hz
Power Consumption	230 W
Fuse	3.15 A
Power Connector In	Power Pro Blue
Power Connector Out	powerCON Grey
DMX Connector	XLR 3P In/Out / XLR 5P In/Out

Mechanical Specifications

Length (mm)	609 mm
Width (mm)	297 mm
Height (mm)	364 mm
Weight	12.7 kg

IP Rating	IP20 (indoor use only)
Housing	Aluminium
Colour	Black

Product Properties

Cooling	Forced Convection
---------	-------------------

Thermal Specifications

Maximum Ambient Temperature	45°C
Minimum Operating Temperature	0°C

Included Items

Included Cables	Power Pro Cable
Included Accessories	Clamp / Controller / Gobo Holder