

Technical Specifications

CCT	2,000K - 10,000K
CRI	≥95
TLCI	≥98
CQS	≥96
SSI (D56)	≥73
SSI (Tungsten)	≥84
TM-30 RF (Average)	93
TM-30 RG (Average)	102
Max Power Output	7.5W
Max Power Consumption	9W
Lumens	770lm
Max Operating Current	1.0A
Operating Voltage	7V
Charging Input	USB Type-C, 5V/2A
Lithium-Polymer Battery	4200mAh 3.7V, 15.5Wh
Battery Life	Approx. 120 Mins @ Max Output
Charge Time	Approx. 120 Mins (5V/2A)
Pixel Mapping	36 Pixels
Operating Temperature	-10° ~ 45°C / 14°F ~ 113°F
Dimming	0-100%
Wireless Operating Range (Bluetooth)	≤80m / ≤262.5ft
Wireless Operating Range (LumenRadio)	≤100m / ≤328ft
Screen Type	OLED
Firmware Upgradeable	Sidus Link
Cooling Method	Passive Cooling
Control Methods	
Control Methods	On-board, Sidus Link App, DMX/RDM, LumenRadio CRMX
Dimensions	
Dimensions	30.0 x 4.0 x 3.5cm / 11.81 x 1.57 x 1.38in
Lamp	30.0 x 4.0 x 3.5cm 11.81 x 1.57 x 1.38in
Weight	
Weight	391g / 0.86lbs
Lamp	391g 0.86lbs