

## Specifications

<b>CCT</b>	2000K – 10000K
<b>G/M Adjustable</b>	±1.00G
<b>Color Modes</b>	HSI, RGB, XY, Gels
<b>CRI</b>	≥ 95
<b>TLCI</b>	≥ 95
<b>CQS</b>	≥ 95
<b>SSI (Tungsten)</b>	84
<b>SSI (D56)</b>	74
<b>TM-30 RF (Average)</b>	95
<b>Beam Angle (Half-Peak Angle)</b>	120°
<b>Max Power Output</b>	600W
<b>Max Power Consumption</b>	720W
<b>Operating Current (AC)</b>	8A
<b>Operating Current (DC)</b>	15A
<b>Operating Voltage (AC)</b>	100V~240V
<b>Operating Voltage (DC)</b>	48V DC
<b>DC Input</b>	48V 15A
<b>Cable Type (AC Power)</b>	Neutrik® powerCON TRUE1 TOP AC Power Cable (6m)
<b>Cable Type (Head Cable)</b>	5-Pin XLR Head Cable (3m)
<b>Operating Temperature</b>	-20°C ~ 45°C / -4°F ~ 113°F
<b>Connectivity</b>	Bluetooth 5.0 (Sidus Mesh), LumenRadio CRMX
<b>Firmware Upgradeable</b>	USB (FAT16/FAT32), Sidus Link
<b>Display Type</b>	OLED
<b>Cooling Method</b>	Active Cooling
<b>Mounting</b>	Junior Pin
<b>Accessory Mount</b>	Nova P600c Accessory Slot
<b>Estimated LED Lifetime (L70)</b>	50,000 Hours
<b>Dimensions</b>	
<b>Lamp Head w/ Yoke</b>	80.20*48.15*17.96cm / 31.57*18.95*7.07in
<b>Lamp Head w/o Yoke</b>	63.97*28.49*16.58cm/□21.18*11.21*6.53in
<b>Panel Surface</b>	63.97*28.49cm/□21.18*11.21in
<b>Control Box</b>	15.75*9.66*4.58cm / 6.20*3.80*1.80in
<b>Lightning Clamp</b>	10.35*8.74*12.5cm/□4.07*3.44*4.92in
<b>Carrying Case</b>	93.75*30.65*64.10cm/□36.91*12.06*25.23in
<b>Weight</b>	
<b>Lamp Head</b>	13.74kg / 30.29lbs
<b>Control Box</b>	0.43kg / 0.947lbs
<b>Case (Empty)</b>	13.7kg / 30.2lbs
<b>Total Weight</b>	27.87kg / 61.44lbs