



# INFINIMAT 8x8 Kit Data Book

## Main Features

- **Modular Full-Color RGBWW LED Mat with Inflatable Softbox**
- 1600W Power Supply
- Lamp Heads Designed With 2x2 Modules to Allow for **Easy Module Replacements**
- **Power and Control Multiple INFINIMATS** Using a Single Control Box (400W and 1600W Control Boxes Available)
- INFINIMAT 1600W Control Box **Supports Battery Operation** via Dual 48V DC Inputs
- **Head-to-Toe IP65** Dust & Water-Resistant Rating for Lamp Head and Control Box
- **Inflatable Softbox Provides Structural Support** for Lamp Head, Diffusion, Light Control Grid, and Light Control Skirt
- **Automatic Pressure Release Valves** on Inflatable Softbox to Prevent Overfilling of Air
- **Included Air Bag Repair Patches** to Ensure Continued Operation of Softbox Even When Punctured
- **Included Light Control Grid** and **Light Control Skirt**
- >90% of Colors Within **Rec.2020 Color Space**
- **Fully Tunable CCT** from 2,000K to 10,000K
- Fully-Tunable **Green-Magenta Adjustment**
- **0.1-100% Stepless** Brightness Control – with Improved Low-End Dimming
- **Advanced HSI** with White Point CCT Control
- **Industry-standard xy** (CIE 1931), RGB, Light Source, & 300+ Gel Presets
- **Multiple Control Methods:** Sidus Link App Control, LumenRadio CRMX, Art-net & sACN via etherCON, 16-bit 5-Pin DMX512 In & Out
- **2 Output Modes:** Max & Constant



## Product Description

The Aputure INFINIMATs is a family of full-color RGBWW pixelated LED light mats with inflatable softboxes. With multiple mat size options, head-to-toe IP65 weather resistance, and the ability to power and control multiple light mats using a single control box, the INFINIMAT family is an adaptable system of lights that are easily deployable in challenging filming environments where fixture weight and set up speed are of the utmost importance.

Each INFINIMAT is designed to seamlessly secure to an inflatable softbox of corresponding size using a hook-and-loop system around the border of the mats. The inflated softbox provides the structural support needed to hold the mat, lighting control grid, and skirt together when the entire unit is rigged overhead or on stands.

Each INFINIMAT also features multiple rigging methods. From a carbon fiber support bracket with a new K-Mount ball head terminating in an extended, knurled baby pin or a TVMP mount, to butterfly, Speed-Rail, and truss frames, all INFINIMATs can be rigged or supported using various methods. Coupled with multiple INFINIMAT sizes to choose from and the ability to stack mats together to create custom soft light source sizes, the INFINIMATs are one of the most versatile fixture families on the market.

Depending on the size of the INFINIMAT, users will have two control box options to choose from: a 400W or 1600W control box. Both control boxes can simultaneously power and control multiple lights at a time with power consumption levels up to the wattage of the control box. This improves cable management workflows as well as reduces the weight and complexity of rigged lighting set ups that call for multiple INFINIMATs. In addition, the 400W control boxes have AC power passthrough, which allow users to daisy chain multiple 400W control boxes together using Neutrik PowerCon cables. This AC power pass through feature further improves the cable management experience of running multiple INFINIMATs as users will only need to run one stinger to an entire array of INFINIMATs.

The INFINIMAT's full-color LED chipset is capable of expanded color controls across its wide 2,000K to 10,000K CCT range with green-magenta adjustment and >90% coverage of colors within the Rec. 2020 color space.

Designed for professional motion picture production, the INFINIMATs feature advanced connectivity options (including Sidus Link app control, LumenRadio CRMX, Art-net & sACN via etherCON, and 16-bit DMX512). And with their rugged IP65 dust and weather-resistant construction, the INFINIMATs can withstand the most demanding filming environments without compromising its performance or reliability.

## Target Audience

The INFINIMATs are ideal for professional lighting technicians and filmmakers who need the most adaptable and brightest full-color LED mat with high rigging versatility and industry-leading color quality.

Professionals working on set will appreciate the cable management efficiency forethought found on the INFINIMATs. With the ability to power multiple lamp heads using a single control box along with AC power passthrough on the 400W control box, users will find managing multiple sets of AC power and head cable to be a much more efficient experience.

Lighting technicians who work in challenging shooting environments where weather resistance and fixture weight are critical decision-making factors will enjoy working with the INFINIMATs' head-to-toe IP65 rating and lightweight nature. With the added benefit of being stackable into custom light source dimensions, the INFINIMATs fill the role of an adaptable, highly maneuverable, and rugged soft light perfectly.

As a family of professional lights, the INFINIMATs can seamlessly sync into existing lighting control workflows with its LumenRadio CRMX, Art-net & sACN via etherCON, and 16-bit DMX512 controls. And with Sidus Link app control, users can easily achieve remote control of INFINIMATs when they are rigged in hard-to-reach places.

From commercials to feature film sets, the IP65-rated INFINIMATs are an industry-leading full-color LED mat family that belong on any professional film production with soft light needs.





## INFINIMAT 8x8 Kit Photometrics

CCT	Dis.	No Modifier	Inflatable Softbox	Inflatable Softbox + Grid
2,000K	3m	5,330 lux 496 fc	4,150 lux 386 fc	3,250 lux 302 fc
	5m	2,339 lux 218 fc	1,758 lux 163 fc	1,393 lux 130 fc
	7m	1,345 lux 125 fc	997 lux 93 fc	778 lux 72 fc
3,200K	3m	6,530 lux 607 fc	5,070 lux 472 fc	4,050 lux 377 fc
	5m	2,869 lux 267 fc	2,138 lux 199 fc	1,705 lux 159 fc
	7m	1,651 lux 154 fc	1,210 lux 113 fc	953 lux 89 fc
4,300K	3m	7,010 lux 652 fc	5,330 lux 496 fc	4,230 lux 393 fc
	5m	3,090 lux 287 fc	2,250 lux 209 fc	1,830 lux 170 fc
	7m	1,730 lux 161 fc	1,270 lux 118 fc	1,008 lux 94 fc
5,600K	3m	7,230 lux 672 fc	5,630 lux 524 fc	4,460 lux 415 fc
	5m	3,170 lux 295 fc	2,385 lux 222 fc	1,895 lux 176 fc
	7m	1,828 lux 170 fc	1,340 lux 125 fc	1,062 lux 99 fc
6,500K	3m	7,040 lux 655 fc	5,490 lux 511 fc	4,350 lux 405 fc
	5m	3,090 lux 287 fc	2,321 lux 216 fc	1,844 lux 171 fc
	7m	1,781 lux 166 fc	1,307 lux 122 fc	1,035 lux 96 fc
10,000K	3m	6,480 lux 603 fc	5,070 lux 472 fc	4,080 lux 379 fc
	5m	2,840 lux 264 fc	2,141 lux 199 fc	1,705 lux 159 fc
	7m	1,635 lux 152 fc	1,210 lux 113 fc	960 lux 89 fc

## What's in the Box

Name	Qty
Flight Case for INFINIMAT & Softbox Pack 8x8	1
Aputure INFINIMAT 8x8	1
Aputure INFINIMAT 15m Head Cable (1600W)	1
Aputure INFINIMAT Inflatable Softbox 8x8	1
Aputure INFINIMAT Light Control Skirt 8x8	1
Aputure INFINIMAT Patch Kit	1
Aputure INFINIMAT Air Pump Max	1
Aputure INFINIMAT Cushion 8x8	1
Rolling Case for Control Box 1600w Pack	1
Aputure INFINIMAT Control Box 1600W	1
AC Cable – 1600W	1
Safety Rope (1.3m)	1
Carrying Case for Control Grid 8x8	1
Aputure INFINIMAT Light Control Grid 8x8	1

## INFINIMAT 8x8 Specifications

CCT	2,000K – 10,000K	
CRI	≥96	
TLCI	≥97	
CQS	≥95	
SSI (Tungsten)	84	
SSI (D56)	73	
TM-30 RF (Average)	92	
TM-30 RG (Average)	100	
Max Power Consumption	2,000W	
Max Power Output	1,600W	
Weather Resistance Rating	IP65	
Pixel Count	16 pixels	
Pixel Module	2x2	
Softbox Inflation Time (Air Pump Max)	2 mins	
Full-Inflation Duration	2 days	
Operating Voltage	DC1 & DC2	12V-16.8V 22V-33.6V
	AC	100V ~ 264V
Operating Temperature	-20°C ~ 50°C	
Storage Temperature	-20°C ~ 85°C	
Control Methods	On-board, Sidus Link App, DMX/RDM, CRMX, etherCON	
Firmware Upgradeable	Sidus Link, USB Drive	
Wireless Range (Bluetooth & CRMX)	≤100m / ≤328.1ft	
Control Box Type	INFINIMAT Control Box 1600W	
Control Box Fan Noise Levels	High Speed Mode	35.9 dBA
	Medium Speed Mode	35.3 dBA
Weight	INFINIMAT 8x8	32.00kg / 70.55lbs
	INFINIMAT Air Pump Max	3.75kg / 8.27lbs
	Control Box	19.38kg / 42.73lbs
	Inflatable Softbox 8x8	9,20kg / 20.28lbs
	Light Control Skirt 8x8	3.45kg / 7.61lbs
	Light Control Grid 8x8	3.50kg / 7.72lbs
	Flight Case	40.00kg / 88.18lbs
Dimensions	INFINIMAT 8x8	239.00 x 239.00cm 7.84 x 7.84ft
	INFINIMAT Air Pump Max	34.8 x 17.8 x 17.8cm 13.7 x 7.0 x 7.0in
	Control Box	27.3 x 26.2 x 55.0cm 10.75 x 10.31 x 21.65in
	Inflatable Softbox 8x8	239.00 x 239.00 x 27.00cm 7.84 x 7.84 x 0.89ft
	Light Control Skirt 8x8	235.00cm x 234.00cm 92.51 x 92.51in
	Light Control Grid 8x8	230.00cm x 230.00cm 7.55 x 7.55ft
	Lamp Head Flight Case	73.00 x 65.00 x 73.00cm 28.74 x 25.60 x 28.74in
	1600W Control Box Case	68.0 x 45.0 40.7cm 26.8 x 17.7 x 16.0in



## Sales & Shipping Information

Shipping Information for Kit								
Product Name	SKU	EAN	Dimension	Netweight	Gross weight	Carton Quantity	Packing Dimension	HS-code / Taric code
INFINIMAT 8x8 Kit (UK)	AP60039AR6	/						
INFINIMAT &Softbox Pack 8x8 (UK)		6971842189939	80x72x92.2cm	106kg	116kg	1	83x75x93cm	9405499000
INFINIMAT Control Box 1600w Kit (UK)		6971842189809	67x42.5x40cm	26.8kg	28.5kg	1	69.5x46.5x42.5cm	8537109090
INFINIMAT Control Grid 8x8		6971842187829	131.6x24.8x24.8 cm	6kg	7kg	2	133.1x51.5x26.6cm	9405990000
INFINIMAT 8x8 Kit (EU)	AP60039AR8	/						
INFINIMAT &Softbox Pack 8x8 (EU)		6971842189953	80x72x92.2cm	106kg	116kg	1	83x75x93cm	9405499000
INFINIMAT Control Box 1600w Kit (EU)		6971842189823	67x42.5x40cm	26.8kg	28.5kg	1	69.5x46.5x42.5cm	8537109090
INFINIMAT Control Grid 8x8		6971842187829	131.6x24.8x24.8 cm	6kg	7kg	2	133.1x51.5x26.6cm	9405990000