

## Product Specifications

**Connectivity**

CRMX, DMX512, Art-Net & sACN via Ethernet and Wifi

**Universe Support**

4 Wireless Universes & 4 Wired Universes

**Ethernet Connectivity**

2x RJ45 Ports at 100Mbps Each

**DMX Connectivity**

4x XLR 5-Pin DMX Bidirectional Female Ports

**Wi-Fi Operating Frequency**

5 GHz at 150Mbps

**CRMX / Sidus BT Operating Frequency**

2.4GHz

**Bluetooth Wireless Range**

≤300m / ≤984ft

**Wi-Fi Wireless Range**

≤800m / ≤2,625ft

**CRMX Wireless Range**

≤800m / ≤2,625ft

**Wi-Fi Modes**

AP mode/STA mode

**CRMX Mode**

TX mode

**AC Adapter Operating Voltage**

AC In: 100-240V DCOut:9V/18W

**DC Jack**

5.5/2.5mm DC Barrel Jack (9-24V) (3m)

**V-Mount**

V-Mount Battery Plate (12-16.8V)

**Lithium Polymer Battery**

3.7V 1500mAH

**Backup Battery Life**

80 min

**Power Consumption**

17W Max, 6W Normal (W/O: Charging, Type-C Output)

**Charge Time**

30 min

**IP Rating**

IP65

**Operating Temperature**

-20°C to 55°C / -4°F to 131°F

**Firmware Upgradeable**

Sidus BT, USB-C, Sidus Link Pro Wifi

**Cooling Method**

Passive Cooling

## Dimensions

**Dimensions (Excluding Antenna)**

18.7 x 18.6 x 6.9cm / 7.4 x 7.3 x 2.7in

## Weight

**Weight**

1.40kg / 8.82lbs