

Product Specifications

CCT	2,700K ~ 6,500K
CRI	≥96
TLCI	≥98
CQS	≥95
SSI (D56)	≥74
SSI (Tungsten)	≥85
TM-30 RF (Average)	95
TM-30 RG (Average)	100
Max Power Output	≤600W
Power Consumption	≤720W
Operating Current	8A
Operating Voltage (Power Supply)	100V~240V, 50Hz/60Hz
Operating Voltage (Battery): V-Mount / Gold Mount (Two Batteries) Half Output	12.5V-16.8V (14.4/15A) 22V-33.6V (26V/8.5A, 28.8V/7.5A)
Operating Voltage (Battery): Voltage V-Mount / Gold Mount (Two Batteries) Full Output	22V-33.6V (26V/18A, 28.8V/16A)
Operating Voltage (3-Pin XLR [48V DC])	48V/15A
Operating Temperature	-20°C ~ 45°C / -4°F ~ 113°F
Battery Charging (Voltage)	16.8V/29.4V
Battery Charging (Amperage)	3A
Wireless Operating Range (2.4GHz)	≤100m
Wireless Operating Range (Bluetooth)	≤80m
Wireless Operating Range (LumenRadio)	≤100m
Screen Type	OLED
Firmware Upgradeable	USB (FAT16/FAT32), Sidus Link OTA
Cooling Method	Active Cooling
Weatherproofing	Dust & Water Resistant
Cable Type: Max Head Cable Length	7.5m
Cable Type: Power Cable	Neutrik® powerCON TRUE1 TOP AC Power Cable (6m)
Accessory Mount Mounting	Bowens Mount 16mm / 28mm 5/8in (Baby Pin) / 1.125in (Junior Pin)
Dimensions	
Lamp Head w/o Yoke	30.2 x 14.7x 14.9cm / 11.88 x 5.78 x 5.86in
Lamp Head w/ Yoke	30.2 x 43.6 x 24.8cm / 11.88 x 17.16 x 5.86in
Control Box	32.3 x 17.9 x 14.2cm / 12.71 x 7.04 x 5.59in
Case	62.5 x 43.5 x 39cm / 24.61 x 17.13 x 15.35in
Weight	
Lamp Head w/ Yoke	5.16kg / 11.37lbs
Control Box	4.89kg / 10.78lbs
Weight (Total w/ Case)	19.07kg / 42.04lbs