

Specifications

[Collapse All](#)

Outputs

2 ohms Stable	No
Output per Channel into 8 ohms at 1 kHz	400 W
Output per Channel into 4 ohms at 1 kHz	600 W
Bridge Output into 8 ohms at 1 kHz	1000 W
Output Channels	4
Output Mode	4-channel, Bridge, Mono, Parallel
Output Connector	Speaker Connector 2 pole , Speaker Connector 4 pole , Terminal

Inputs

Mono Inputs	4
Transformer	100 V
Mono Input Connector	3-pin XLR, Terminal
Mono Input Gain Range	32 dB

Audio Specifications

THD Level %	< 0.003 %
Signal-to-noise Ratio	> 103 dB
AD/DA Convertor Sample Rate	48 kHz
Slew Rate	25 V/ μ s
Amp Technology	Class D
Damping Factor	190 :1
Frequency Response Minimum	20 Hz
Frequency Response Maximum	25000 Hz

Software Specifications

Supported Operating Systems	Mac, Windows, Windows 10, Windows 11
-----------------------------	--------------------------------------

Sound Editing

DSP	Yes
Parametric Input Equalizer	10 Bands
Parametric Output Equalizer	10 Bands
Crossover Slopes	24 dB
Dynamics Processing	Compressor, Limiter
Output Delay (Max.)	10 ms
Input Delay (Max.)	10 ms

Internal Storage

User Presets	Yes
User Presets Capacity	100

Control and Programming

Control Mode	PC Software
--------------	-------------

Electrical Specifications and Connections

Power Supply	230 V AC 50 Hz
SMPS	No
Power Consumption	1100 W
Fuse	8 A
Power Connector In	Power Pro Blue
Data Connector In	RJ45

Mechanical Specifications

Amplifier Airflow	Front to back
Amplifier Cooling	Radial Fan
Height (mm)	45 mm (1.772")
Width (mm)	482 mm (18.976")
Depth (mm)	300 mm (11.811")

Installation Depth (Excl. Connector)	315 mm (12.402")
Flightcase Size	19"
Rack Units	1 U
Housing	Metal
Colour	Black
Weight	4.7 kg (10.362 lb)
IP Rating	IP20 (indoor use only)

Product Properties

Handles	No
Electronic Protection	Clip limiter, Short circuit
LED Indicators	Clip, Ethernet, Output level, Power, Protect

Included Items

Included Cables	Power Pro Cable
------------------------	-----------------