


MULTICORE SPEAKER CABLES

CVS LK**N**



CVS LKCode		04N25	04N40	06N25	06N40	08N25	08N40	16N40	
GENERAL DATA									
Cable	O.D.	11.10 mm	13.20 mm	14.20 mm	15.50 mm	16.00 mm	19.50 mm	21.50 mm	
	Standard reels	200 m						152 m	
	Weight	kg/100m	21.50	34.50	35.00	47.60	47	65.50	93.90
	Operating temperature	5°C/+70°C							
Jacket	Material	PVC fire resistant							
	Nominal Thickness	≥ 1.20 mm	≥ 1.80 mm	≥ 1.60 mm	≥ 1.50 mm	≥ 1.60 mm	≥ 1.80 mm	2.20 mm	
Conductor	D.C.R. [ohm/km] at 20° C	8	5	8	5	8	5		
	Quantity	4		6		8		16	
	Strand	80 x 0.2 mm	128 x 0.2 mm	80 x 0.2 mm	128 x 0.2 mm	80 x 0.2 mm	128 x 0.2 mm	80 x 0.2 mm	
	Area/AWG	2.50 mm ² /13	4.00 mm ² /11	2.50 mm ² /13	4.00 mm ² /11	2.50 mm ² /13	4.00 mm ² /11	4.00 mm ² /11	
	Insul. O.D.	3.4	4.0	3.4	4.0	3.4	4.0	4.0	
	Material	PVC fire resistant							