Specifications

Collapse All

Source

Light Source Type	LED
Light Source Quantity	1
Light Source Power	300 W
LED Colour Type	WW
Light Source System	COB
Life Expectancy	50000 h
Refresh Rate (Max.)	25 kHz
Illuminance @ 5 m	3890 lx
Luminous Flux (Total)	11000 lm
CRI	98
Maximum CCT	3200 K

Optical

Zoom Type	Manual
Zoom Minimum	15 °
Zoom Maximum	60 °

Control and Programming

Control Mode	DMX
DMX Channels	1, 2, 5
Protocols	DMX, RDM
Display	OLED
Dim Curve	Linear, Square, I-Square, S-Curve
Dimmer Resolution	8 bit, 16 bit

Dynamic Effects

Dimmer	0-100 %

Strobe	0-25 Hz

Electrical Specifications and Connections

Power Supply	120-250 V AC 50/60 Hz
Power Consumption	220 W
Power Connector In	Power Pro True
Power Connector Out	Power Pro True
DMX Connector	XLR 3P In/Out, XLR 5P In/Out
DMX Connector In	XLR 3P, XLR 5P
DMX Connector Out	XLR 3P, XLR 5P

Mechanical Specifications

Length (mm)	417 mm (16.417”)
Width (mm)	286 mm (11.26”)
Height (mm)	260 mm (10.236”)
Weight	6.6 kg (14.55 lb)
IP Rating	IP20 (indoor use only)
Material	Aluminium
Housing	Aluminium
Colour	Black

Product Properties

Cooling	Forced Convection

Rigging

Mounting Options	Bracket
Safety Attachment	Yes
Safety Eyes	1

Product Compliance

Energy efficiency class	T/B/D

Thermal Specifications

Maximum Ambient Temperature	45 °C (113 °F)

Included Items

Included Cables	Power Pro Cable
Included Accessories	Filterframe