



ACCLAIM LED ZOOMSPOT



A successor to the iconic Acclaim, this LED zoomspot luminaire offers high output and full color mixing in a single, cost-effective fixture designed for precision key lighting and gobo projection. With a built-in manual zoom and focus and a four-blade manual shutter system, the Strand Acclaim LED Zoomspot is the perfect choice for small to medium-sized schools, theatres, and houses of worship.

The manual shutter system and integrated 25° to 50° manual zoom and focus on the Acclaim LED Zoomspot gives superior control to shape and focus the light. This provides precise adjustment of the flat, even beam to key light performers or highlight parts of the set. With the optional angle-adjusting gobo holder, designers can project depth and texture on the stage using industry-standard size B metal gobos. And for applications with a shorter trim height, the integrated adjustable yoke allows the fixture to be hung closer to the suspension position. The Acclaim LED Zoomspot is available in black or white.






ACCLAIM LED ZOOMSPOT

FEATURES AND BENEFITS

- **500W/650W-equivalent LED zoomspot from Strand** - cost-effective all-in-one profile from the original name in theatrical lighting
- **Integrated 25° to 50° manual zoom and focus** - precise beam sizing and edge softness control
- **Four-blade manual shutter system** - superior control to position the light only where you need it
- **Optional angle-adjusting size B metal gobo holder** - add depth and texture using industry-standard gobos. Easily adjust gobo holder to get your gobo at the perfect angle.
- **Adjustable yoke** - mount fixture where you want it even when headroom is limited
- **Custom LED light source and RGBL color mixing system** - consistent output and color mixing with the entire Acclaim LED Series
- **Available in black or white** - the perfect body color for your application

LIMITED WARRANTY

Every Strand product is backed by a minimum 2-year limited warranty against manufacturing defects and workmanship. Refer to the Strand Limited Warranty Card available at www.strandlighting.com/global/support/warranty for more details.





ACCLAIM LED ZOOMSPOT

SOURCE

Type	LED
Color	RGBL
Wattage	150W
Frequency adjustment	500Hz to 4000Hz (Default 1500Hz)

OPTICAL PERFORMANCE

Output lumens, max	6500 (Beam) 8500 (Field) (Calibration on)		
Light quality	7100K/RGBL (FULL ON)	5600K / RGBL	3200K / RGBL
CRI (RA)	84	84	84
TM30 Rf	79	80	82
TM30 Rg	102	109	115
CQS	80	80	86
TLCI	77	78	74

BEAM

Zoom range	10° to 50°
Zoom operation	Manual control
Focus operation	Manual control
Accessory holder	Dual rail holder + gel frame (optional extra)
Gobo gate	B size

COLOR

Color mixing type	RGBL
-------------------	------

COOLING SYSTEM

Type	Forced air	
Fan control, default	Auto ramping (default) Continuous spin (on)	
Fixture output modes	Standard*	42.6 dBa
	Studio*	37 dBa
	Whisper*	33.2 dBa



*Maximum dBa level @ 1m (Fan On); base level 21 dBa

POWER

Range	100-240 VAC
Power connector	Twist lock black and yellow; In + Thru
Max wattage	170W
Standby wattage	8.8W



ACCLAIM LED ZOOMSPOT

DATA		
Control protocols	DMX (RDM)	
Data connections	5-pin XLR In/Thru	
Control modes	8-bit - (8 channels) 16-bit - (11 channels)	
PHYSICALS		
Body color options	Black, white	
Yoke	Adjustable height	
ENVIRONMENT		
	°C	°F
Operating temperature range	-10 to 40	14 to 104
Ingress protection rating	IP20	
DIMENSIONS (H x W x D)		
	mm	in
Fixture only	253 x 190 x 353	10 x 7½ x 13¾
Fixture + yoke	356 x 251 x 353	14 x 9¾ x 13¾
WEIGHT		
	kg	lb
Fixture only	5.8	12.78
APPROBATION		
Listings	ETL (UL & CSA)CB/IECEE Scheme for CE-LVD, FCC, ICES, RCM, CE-EMC, UKCA, RoHS, ISO 9001	
		

PRODUCT NAME	ORDER CODE
Acclaim LED Zoomspot black body	64511-002
Acclaim LED Zoomspot white body*	64511-102

*white option by special order only

ACCESSORIES	ORDER CODE
Acclaim LED Zoomspot accessory holder + Gel Frame (Black)	64511-011
Acclaim LED Zoomspot accessory holder + Gel frame (White)	64511-111
Acclaim LED Zoomspot/PLE B Size gobo holder	64511-012
Acclaim LED Zoomspot/PLE 16 leaf iris	64511-013



ACCLAIM LED ZOOMSPOT

PHOTOMETRIC DATA (CALIBRATION ON)

For full photometric reports, visit the [product page](#) on our website.

NARROW ZOOM

LED TYPE	CANDELA	FIELD LUMENS	BEAM LUMENS	CRI(RA)
7100K / RGBL (full on)	37,068	8,415	4,736	84
3200K / RGBL	28,893	7,874	4,831	84
5600K / RGBL	28,057	7,879	4,746	84

7100K (FULL ON)

Throw Distance	ft	10.0	15.0	20.0	30.0
	m	3.0	4.6	6.1	9.1
Field Diameter	ft	4.5	7.0	8.8	13.1
	m	1.4	2.1	2.7	4.0
Illuminance	fc	371	165	93	41
	lux	3,990	1,773	998	443

3200K

Throw Distance	ft	10.0	15.0	20.0	30.0
	m	3.0	4.6	6.1	9.1
Field Diameter	ft	4.8	7.0	8.8	13.1
	m	1.4	2.1	2.7	4.0
Illuminance	fc	288	123	70	31
	lux	3,100	1,319	750	328

5600K

Throw Distance	ft	10.0	15.0	20.0	30.0
	m	3.0	4.6	6.1	9.1
Field Diameter	ft	4.5	7.0	8.8	13.1
	m	1.4	2.1	2.7	4.0
Illuminance	fc	281	119	68	31
	lux	3,020	1,284	730	328



ACCLAIM LED ZOOMSPOT

MEDIUM ZOOM

LED TYPE	CANDELA	FIELD LUMENS	BEAM LUMENS	CRI(RA)
7100K / RGBL (full on)	16,165	8,415	4,732	84
3200K / RGBL	16,165	7,879	4,750	84
5600K / RGBL	15,745	414	3,930	85

7100K (FULL ON)

Throw Distance	ft	10.0	15.0	20.0	30.0
	m	3.0	4.6	6.1	9.1
Field Diameter	ft	4.5	7.0	8.8	13.1
	m	1.4	2.1	2.7	4.0
Illuminance	fc	162	72	40	18
	lux	1,740	773	435	193

3200K

Throw Distance	ft	10.0	15.0	20.0	30.0
	m	3.0	4.6	6.1	9.1
Field Diameter	ft	4.8	7.0	8.8	13.1
	m	1.4	2.1	2.7	4.0
Illuminance	fc	165	70	40	18
	lux	1,780	757	431	193

5600K

Throw Distance	ft	10.0	15.0	20.0	30.0
	m	3.0	4.6	6.1	9.1
Field Diameter	ft	4.5	7.0	8.8	13.1
	m	1.4	2.1	2.7	4.0
Illuminance	fc	162	69	39	18
	lux	1,740	740	421	189



ACCLAIM LED ZOOMSPOT

WIDE ZOOM

LED TYPE	CANDELA	FIELD LUMENS	BEAM LUMENS	CRI(RA)
7100K / RGLB (full on)	8,955	8,415	6,412	84
3200K / RGLB	7,395	7,847	4,549	84
5600K / RGLB	7,274	7,879	4,525	85

7100K (FULL ON)

Throw Distance	ft	10.0	15.0	20.0	30.0
	m	3.0	4.6	6.1	9.1
Field Diameter	ft	4.5	7.0	8.8	13.1
	m	1.4	2.1	2.7	4.0
Illuminance	fc	90	40	22	10
	lux	964	428	421	107

3200K

Throw Distance	ft	10.0	15.0	20.0	30.0
	m	3.0	4.6	6.1	9.1
Field Diameter	ft	4.8	7.0	8.8	13.1
	m	1.4	2.1	2.7	4.0
Illuminance	fc	74	31	18	8
	lux	796	339	193	87

5600K

Throw Distance	ft	10.0	15.0	20.0	30.0
	m	3.0	4.6	6.1	9.1
Field Diameter	ft	4.5	7.0	8.8	13.1
	m	1.4	2.1	2.7	4.0
Illuminance	fc	73	31	18	8
	lux	783	333	189	85

©2021 Signify Holding. All rights reserved.

All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

Ref: 64511-002-100-00