FUTURELIGHT WDR-CRMX RX IP Wireless DMX Receiver Outdoor

Weather-proof wireless DMX receiver, IP65

Art. No.: 51834032

GTIN: 4026397722550











List price: 296.31 €

incl. 19% VAT.

Features:

- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Control via CRMX by LumenRadio; RDM
- Can receive and process up to 512 DMX channels
- Lockable power input (IP T-Con)
- With Omega bracket
- Operating range up to 600m with line-of-sight
- Suitable for outdoor use IP65
- 2.4 GHz license-free worldwide

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x declaration of conformity

Logistic

EAN / GTIN: 4026397722550
Weight: 1,55 kg
Length: 0.30 m
Width: 0.20 m
Heigth: 0.14 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	1,6 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
DMX channels:	Input 512
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Control:	CRMX by LumenRadio; RDM
Attachment system:	Omega bracket
Status LED:	DMX; level meter
Frequency band:	2.4 GHz
Modulation:	GFSK
Antenna gain:	5 dBi
Range:	Range up to 600m with line-of-sight
Color:	Black
Dimensions:	Length: 17,3 cm Width: 15,6 cm Height: 9,2 cm
Weight:	1,30 kg

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.