



M-7X^{RGBA}

STAGE FOGGER

The M-7X RGBA is the upgraded version of M-7 RGBA LED fog machine.

With the improved heater, it can deliver more powerful, higher volume, and much quicker fog bursts.

Feature

- Neutrik TRUE 1 Connector
- RGB LEDs on board.
- Optional Wireless DMX available.
- New structure design for multiple angle rigging
- Auto sensing frequency
- Fluid tank compartment for ease of transportation
- Huge output volume with high pigments LED colors
- Great fit for Stage purpose
- Generate fog at any orientation



Neutrik TRUE 1 Connector



Specification

- | | |
|------------------------|---|
| - Input voltage | US model : AC 100-120V, 50 / 60Hz 13A
EU model : AC 220-240V, 50 / 60Hz 6.5A |
| - Rated power | 1516W |
| - Light source | 22 x 3W LED (5 Red, 6 Green, 6 Blue, 5 Amber) |
| - Warm-up time | 7 minutes (approx.) |
| - Fluid consumption | 200 ml/min |
| - Fluid tank capacity | 2.4L (0.63gal) |
| - Compatible fluid | Antari FLC Super Light Fog Fluid |
| - Ambient temp. range | 0°C - 40 °C (32 °F-104 °F) |
| - Output | 10 meters height |
| - Control | DMX512, Timer, Manual, Wireless, Master/Slave
Wireless DMX (Optional) |
| - DMX channels | 9 channels |
| - Connection | Neutrik TRUE 1 Connector (Power)
XLR 3-pin and 5-pin (DMX) |
| - Optional accessories | WTR-90 Wireless DMX |
| - Dimension | L344 W193 H381 mm
(L13.54 W7.60 H15 inch) |
| - Weight | 14 kg (30.8 lbs) |