

Technical Specifications

CCT	2,000K - 10,000K
CRI	96
TLCI	96
CQS	95
SSI (D56)	72
SSI (Tungsten)	82
TM-30 RF (Average)	94
TM-30 RG (Average)	103
Lumens	563 lm
Max Power Output (Fixture)	5W
Max Power Output (Case)	100W
Max Power Consumption (Fixture)	7W
Max Power Consumption (Case)	129W
Max Operating Current	0.84A
Operating Current (Fixture)	0.84A
Operating Current (Case)	1.8A
Operating Voltage (Fixture)	3.0-4.2V
Operating Voltage (Case)	12-28V
Charging Input	USB Type-C (5V/2A), Contact Charger
AC Input Voltage	100-240V, 50/60Hz
Lithium-Polymer Battery	4,200mAh / 3.7-4.2V, 15.5Wh
Battery Life (Fixture)	Approx. 120 Mins @ Max Output
Charge Time	Approx. 90 Mins (5V/2A)
IP Rating	IP65
Operating Temperature	-20°C~45°C / -68°F~113°F
Dimming	0-100%
Wireless Range (Bluetooth)	≤80m / ≤262ft
Wireless Range (LumenRadio)	≤100m / ≤328ft
Screen Type	TFT
Firmware Upgradeable	Sidus Link
Cooling Method	Passive Cooling
Control Methods	
Control Methods	On-board, Sidus Link App, DMX/RDM, LumenRadio CRMX
Dimensions	
Dimensions (Case)	43.5 x 38.5 x 15.0cm / 17.1 x 15.1 x 5.9in
Dimensions (Fixture)	10.8 x 7.0 x 2.5cm / 4.25 x 2.76 x 0.98in
Weight	
Weight (Case)	5.2kg / 11.5lbs
Weight (Fixture)	247g / 0.54lbs
Weight (Total)	9.3kg / 20.5lbs