

# Specifications

[Collapse All](#)

## Source

---

Light Source Type	LED
Light Source Quantity	1
Light Source Power	150 W
LED Colour Type	RGBAL
Refresh Rate (Max.)	1 kHz
Illuminance @ 3 m	3260 lx
Luminous Flux (Total)	3571 lm
CRI	91
Minimum CCT	2700 K
Maximum CCT	10000 K

## Optical

---

Beam Angle Minimum (Circular)	23 °
Beam Angle Maximum (Circular)	46 °
Zoom Type	Manual
Zoom Ratio	1:2
Zoom Minimum	23 °
Zoom Maximum	46 °

## Control and Programming

---

Control Mode	DMX, Manual, RDM
DMX Channels	5, 8, 12
Protocols	DMX, RDM
Display	OLED
Display Size	1.3 "
Dimmer Resolution	16 bit

## Dynamic Effects

---

Dimmer	0-100 %
--------	---------

## Electrical Specifications and Connections

---

Power Supply	100-240 V AC 50/60 Hz
Power Consumption	180 W
Fuse	3.15 A
Power Connector In	Power Pro Blue
Power Connector Out	Power Pro Grey
DMX Connector	XLR 3P In/Out
DMX Connector In	XLR 3P
DMX Connector Out	XLR 3P

## Mechanical Specifications

---

Length (mm)	523 mm (20.591")
Width (mm)	225 mm (8.858")
Height (mm)	373 mm (14.685")
Weight	6.15 kg (13.558 lb)
IP Rating	IP20 (indoor use only)
Housing	Aluminium, Metal
Colour	Black

## Product Properties

---

Cooling	Forced Convection
---------	-------------------

## Rigging

---

Mounting Options	Bracket
Safety Attachment	Yes
Safety Eyes	1

## Thermal Specifications

---

Maximum Ambient Temperature	40 °C (104 °F)
-----------------------------	----------------

## Included Items

---

Included Cables	Power Pro Cable
-----------------	-----------------