



Special features

- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Powerful and intense colours, incl. pastel tones
- Suitable for 24 V colour controllers
- Suitable for event spaces, reception rooms, hallways

Housing Material	Aluminium
Housing Color	White
Material of Lens	PMMA
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input	94 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Dimmable	Yes
Control	Dimmable via optional controller
Motion Detector	No

Working Temperature	-20 to 45 °C
Storage Temperature	-40 to 80 °C
IP Protection Class	IP 40

Light Source	LED, Light source not changeable
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	4200 lm
Luminous Efficiency	44.7 lm/W
Rated Angle of Reflection	110 Degree
Light Distribution	Symmetric

Life Time L70 / B50	50000 h
Switching Cycles	100000
Power Consumption	94 kWh/1000h
EEL	F

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	595 mm
Width	595 mm
Height	11 mm
Product weight	2871 g